



REAR FRAME

- Bolted rear frame – no welding
- Mill finish or anodised vertical aluminium uprights
- Top and bottom cross-members are either galvanised steel or stainless steel
- 270° opening barn doors in 30 mm insulated panel
1 stainless steel recessed lock on right door leaf

OPTIONAL EXTRAS

- Steel rear frame
- Top flap in combination with tail-lift
- Roller shutter door
- No rear frame – solid panel front and rear

SIDE WALLS

- 6 mm Fibreglass Reinforced Plywood panels GRP on both faces,
Vertical aluminium uprights (22,5 x 38) bonded at the interval of 580 mm and fitted to the top and bottom profiles
Smooth surfaces on all external panels (colour based on white RAL 9010)

OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protection for removing cargo
- Single swing door, double swing door or sliding door



6 MM FRP PANEL Kit

Range : 6,5 tonne GVW rating max.
Family : FRP panel + vertical uprights
Execution : **EUROPAL**

BODY DIMENSIONS (mm)

External length : 1 500 to 6 000 mm
External width : 2 350 mm max.
Internal height :
2 350 mm max. with top flap
2 400 mm max. with 2 barn doors

FRONT BULKHEAD

- 14 mm FRP panel (colour based on white RAL 9010)

OPTIONAL EXTRAS

- 6 mm FRP panel + 5 vertical uprights
- Lashing rails, lashing tubes, interior protection for removing cargo
- Upward opening access – sliding access
- Polyester nose cone

ROOF

- Mill finish or anodised aluminium profiles
- One piece semi-translucent or white opaque roof riveted to the roof frame

OPTIONAL EXTRAS

- Clear light or translucent strip
- 30 mm insulated panel
- Ceiling light (12 LED lamps)

SUB-FRAME (optional extra)

- Mill finish aluminium sub-frame in kit format
- Aluminium longitudes
- Aluminium cross-members

OPTIONAL EXTRAS

- Mudwings - side-guards
- Footsteps (4 rungs)

