



## Kit POLYESTER

**Range :** GVW 6,5 ton ratings max.

**Family :** Polyester

**Execution :** **EUROPAL**



### DIMENSIONS (mm)

External length : 4 500 mm max.

External width : 2 350 mm

Internal height : 2 300 mm max.

### REAR FRAME

- Bolted rear frame – no welding
- Mill finish or anodized aluminium uprights
- Top and bottom cross-members in galvanized steel or stainless steel
- 270° opening barn doors in 30 mm insulated panel
- 1 stainless steel recessed lock on right door leaf

### OPTIONAL EXTRAS

- Steel rear frame
- Top flap in combination with tail-lift
- Roller shutter door
- No doors – rear panel same as front

### SIDE WALLS

- 3 mm polyester skin – 2 sides
- Vertical aluminium square tubes (40x25) bonded at a pitch of 460 mm and fitted to the top and bottom rails
- Smooth external face (close to colour white RAL 9016)

### OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protections for removal box
- Side door : single swing – Clear width 1030 mm



### FRONT BULKHEAD

- Polyester skin (close to colour white RAL 9016) or 14 mm Fibreglass Reinforced Plywood panel

### OPTIONAL EXTRAS

- Lashing rails, lashing tubes, interior protections for removal box
- Trap door – sliding trap door (14 mm FRP panel only)
- Polyester nose cone

### ROOF

- Mill finish or anodized aluminium profiles
- One piece aluminium or translucent roof riveted to the roof frame

### OPTIONAL EXTRAS

- Insulated roof (steel rear frame only)
- Clear light or translucent strip
- Ceiling light (4 LED lamps)

### SUB-FRAME (Optional extra)

- Mill finish aluminium sub-frame in kit format
- Main beams in aluminium
- Cross-members in aluminium or galvanized steel

### OPTIONAL EXTRAS

- Mudwings - side-guards
- Footsteps (4 rungs)

